

Safe Operating Procedure Air Rammer

www.rapidhire.net.au

We are located at:
10 Kerryl Street, Kunda Park Qld 4556
Email: info@rapidhire.net.au
Phone: 07 5456 2664



The instructions recommended within this document apply to normal risk conditions. If the Air Rammer is to be operated in a dangerous or hostile environment, the user/client is responsible for conducting an appropriate risk analysis and applying suitable controls to mitigate those additional risks.







This instruction should be read in conjunction with the Risk Assessment procedure for the Air Rammer.

Safety risks:

- Moving, rotating & sharp parts
- Noise
- Compressed Air
- Manuel handling

WARNING: Do not wear loose fitted clothing or jewellery and ensure long hair is contained

You must wear this personal protective equipment when doing this task:

| Foot Protection | Hearing Protection | High Visibility | Eye Protection | Hand Protection | Dust Mask |
|--|--|--|--|---|--|
|  |  |  |  |  |  |

Pre-Operational Check:

- ✓ Ensure task (e.g. Drawings, instructions, specifications etc) is clearly understood.
- ✓ Check that the accessories and attachments are properly fitted and that all guards and other safety devices are in place and working properly.
- ✓ Before you inspect any parts, make sure the power to the air compressor is turned off and the lead unplugged from the power source.
- ✓ Lock the wheels on the base of the compressor to prevent movement.
- ✓ Check all fittings are securely connected prior to being pressurized.
- ✓ Check fuel level (if applicable) and/ or power supply.
- ✓ Check workspace and walkways to ensure no slip/trip hazards are present. Ensure adequate lighting. Remove any flammable liquids or combustible materials from the near proximity.
- ✓ Identify ON/OFF switch and emergency stop button.
- ✓ Ensure all other employees are clear of the immediate work area.

Safe Operation:

1. Do not use in close proximity to other workers.
2. When you start up the compressor, listen for unusual noises or vibrations.
3. Start the compressor noting pressure increase and cut-out/cut-in pressure.
4. Listen for any air leaks from any flexible airlines and immediately report if any leaks are observed.
5. Do not blow compressed air on skin.
6. Grasp handles at corner of handles when operating – use “loose” grip to reduce stress and vibration on hands, wrists and arms from machine.
7. Always use two hands. Ensure you have a firm footing and are always ready to handle any reaction the tool may make.

Safe Operating Procedure Air Rammer

www.rapidhire.net.au

We are located at:
10 Kerryll Street, Kunda Park Qld 4556
Email: info@rapidhire.net.au
Phone: 07 5456 2664



8. Operators should be prepared to brace themselves against the high level of torque exerted by the tool.
9. Apply slight pressure on the tool. Pressing very hard will not increase efficiency. Stop operation if the tool bounces around uncontrollably.
10. Always walk behind rammer, and allow machine to pull itself forward.
11. Operate so that shoe hits ground flat for best compaction, and not on toe or heel.
12. Reduce tool speed to slow if rammer needs to be lifted during operation.
13. Do not touch immediately after operation. It may be extremely hot.
14. To Stop, release the handle grip. Disconnect air hose and turn off compressor after use.
15. Use legs to move machine – do not force by using arms and shoulders only.
16. Avoid breathing dust – wear suitable dust mask or respirator in dusty areas.
17. Be aware that this tool is designed to create severe vibration. The hands, arms and legs will quickly tire. Take regular breaks.
18. Don't over-reach or work at an awkward angle.
19. Keep your hands and feet away from moving parts at all times.
20. Ensure good housekeeping practices are in place to minimize waste build-up.

Storage & Maintenance:

1. Disconnect tool from air compressor, disconnect air compressor from power supply before packing away.
2. Turn off air supply.
3. Avoid breathing dust (especially concrete dust) when cleaning and moving machine.
4. Secure machine against movement when transporting.

Air Rammer Risk Assessment

www.rapidhire.net.au

We are located at:
 10 Kerryl Street, Kunda Park Qld 4556
 Email: info@rapidhire.net.au
 Phone: 07 5456 2664



| Likely Risk Issue | Who/ What may be harmed? (Specific Persons) | What is the Rate Level? (Rate risk as Low, Medium or High) | What Risk Control Actions Needs to Be Taken? (What needs to be considered so that the risks are identified and effectively controlled) | Time Frame |
|---------------------------|--|--|--|------------|
| Electrocution | Participants Operators Spectators Staff | Severity of Risk (S) – 2 Likelihood of Risk (L) – 2 Overall Risk (S x L) = 4 MEDIUM | <ul style="list-style-type: none"> Operator to check for damaged air lines prior to use Immediately isolate equipment from the main power supply and DO NOT USE Report to Rapid Hire management immediately Ensure compressor is in a well ventilated area and clear of obstruction | Each hire |
| Noise | Participants Operators Spectators Staff | Severity of Risk (S) - 2 Likelihood of Risk (L) - 2 Overall Risk (S x L) = 4 MEDIUM | <ul style="list-style-type: none"> Ensure adequate hearing protection is worn | Each hire |
| Rotating and moving parts | Participants Operators Spectators Staff | Severity of Risk (S) - 3 Likelihood of Risk (L) - 2 Overall Risk (S x L) = 6 MEDIUM | <ul style="list-style-type: none"> Ensure equipment is maintained and in good condition before use DO NOT USE FAULTY EQUIPMENT. REPORT IMMEDIATELY Use equipment as per manufacturers recommendations All necessary guards & safety devices are in place protecting workers from all moving & rotating parts. “Safe Working Zones” are clearly defined in all work spaces where air rammer is being used. And protection barriers where required. Operators are required to remove all jewellery, tuck in loose clothing & tie back long hair. Never run the equipment in excess Wear correct PPE | Each hire |
| Slips, Trips and falls | Participants Operators Spectators Staff | Severity of Risk (S) - 1 Likelihood of Risk (L) - 2 Overall Risk (S x L) = 3 LOW | <ul style="list-style-type: none"> Wear appropriate footwear Slip resistant flooring is encouraged in workspaces Ensure appropriate cleaning and housekeeping practices are maintained to minimise the risk of slips, trips and falls | Each hire |

Calculation of Risk Evaluation

Severity of Risk (S) is judged by evaluating the effects of the hazard if the risk occurs. This is evaluated as Minor = 1, Major = 2, Serious = 3

Risk Likelihood (L) - The likelihood of the harm occurring is evaluated on the basis of: Unlikely =1, Possible = 2, Likely = 3

Overall Risk is calculated by multiplying the figure for Severity (S) and Likelihood (L).

The overall risk figure calculated is related to the Risk Level of either Low: 1 to 3; Medium: 4 to 6 or High: 7 to 9

NB This is a generic risk assessment only. It is advisable to carry out a site-specific assessment prior to using this equipment.